



image not found or type unknown

**LAVE-VAISSELLE À CAPOT DOUBLE
PAROI AVEC POMPE DE VIDANGE**

image not found or type unknown

**HOODED DISHWASHER DOUBLE
WALLED DOOR WITH DRAIN PUMP**

- Châssis et carrosserie en acier inox AISI 304
- Bras de lavage et de rinçage en acier inox
- Porte et cuve en double paroi
- Contrôle numérique
- 3 programmes de lavage
- Résistance cuve et surchauffeur en Incoloy 800
- Rendement 20 casiers par heure
- Dotation 2 paniers 500 x 500 mm (22 assiettes diam 24 / panier)
- Résistance de la cuve 2 500 W
- Résistance du surchauffeur 8 300 W
- Dispositif d'attente surchauffeur
- Isolation thermique sur surchauffeur
- Thermostat cuve à réglage fixe 55°C
- Cuve emboutie à vidange automatique
- Doseur produit lessiviel
- Doseur produit de rinçage
- Durée de cycle 60/120/180 secondes
- Production 1320/660/440 panier par heure
- Contenance de la cuve 26 litres
- Consommation eau de rinçage 3 litres
- Filtres de surface inox dans la cuve
- Prédiposition pour alimentation monophasée
- Puissance 8 900 W / 400 V
- Dimensions L 626 x P 755 x H 2 155 mm
- Poids 200 Kg

Conseil : eau d'alimentation 10-40°C

> Prédiposée pour connexion aux tables accessoires (étagère de service, tables de déchets, etc.)

Référence article : CLVACDPV
EAN : 3611630038768

- Chassis and body : AISI 304 stainless steel
- Washing and rinsing stainless steel arms
- Double walled door and tank
- Digital control
- 3 wash programs
- Tank and boiler heating element : incoloy 800
- Performance : 20 baskets per hour
- supplied : 2 baskets 500 x 500 mm
- Tank heating element : 2,5 kW
- Boiler heating element : 8,3 kW
- Boiler holding device
- Boiler thermal insulation device
- Thermostat bowl with fixed setting 55 ° C
- Deep-drawn tank with automatic draining
- Cleaning products batcher
- Rinsing products batcher
- Cycle times : 60/120/180 secondes
- Production : 1320/660/440 basket per hour
- Tank capacity : 26 liters
- Consumption : 3 liters rinsing water
- Stainless steel surface filters in the tank
- Power : 8,9 kW / 400 V
- Dimensions : L 626 x D 755 x H 2155 mm
- Weight : 200 Kg

Advice: supply water 10-40 ° C

> Predisposed for connection to accessories tables (service shelves, garbage tables, etc.)

Article reference : CLVACDPV
EAN : 3611630038768